

SPECIFICATIONS			
Model	BH5	BH6	BH7
Recommended Tractor HP	Sub-Compact 18HP thru 24HP	25HP+	30HP+
3 Point Hitch	Cat I	Cat I / Cat II	Cat I / Cat II
Digging Depth* (B)	5.5 ft	6.5 ft	7.5 ft
Overall Reach Out (A)	7'7"	9'0"	10'7"
Operating Height UP (C)	8'4"	9'11"	10'7"
Swing Arc (Dual Cylinder)	140 Degrees	180 Degrees	170 Degrees
Stabilizer Width	59"	59"	59"
Dipper Boom Digging Force	880 lbs.	1,385 lbs.	1,875 lbs.
Bucket Digging Force	2,245 lbs.	2,450 lbs.	2,750 lbs.
Bucket Lift Capacity Extended	650 lbs.	800 lbs.	1,100 lbs.
Bucket Size Included	7"	12" – 4 Teeth	16" – 3 Teeth
Included Bucket Capacity	0.79 (Cu Ft)	1,0 Cu Ft	1,10 Cu Ft
Bucket Rotation	160"	195°	195°
Cylinder Diameters	(1) 2.5"	3"	3"
Valve Control Valve Type	(2) (4-Way & (2) 2-Way Joystick	(2) (4-Way & (2) 2-Way Joystick	(2) (4-Way & (2) 2-Way Joystick
Hydraulic Tank Capacity	4 Gallon	4 Gallon	6 Gallon
Hydraulic Pump Details	PTO Driven w/In-Line Filter	PTO Driven w/In-Line Filter	PTO Driven w/In-Line Filter
Optional Bucket Sizes	24" ONLY	24" ONLY	24" ONLY
Warranty	1 Year	1 Year	1 Year
Weights	750 lbs.	1000 lbs.	1250 lbs.
*Digging Depth varies based on overall rear tire height		Measurements based on 16" ground clearance from Boom-Tower	